

Durawash

The DURAWASH simulates the conditions necessary to meet leading chain stores standard garment and fabric durability tests. The process control systems provide excellent accuracy and repeatability.

The physical performance of the DURAWASH is compatible with that of the 'Hoovermatic' Twin Tub and complies with the Marks and Spencer Fabric Durability (C15) and Print Durability (P5) methods of test. The agitator speed is 560rpm +/-5%.

The DURAWASH incorporates a control console, which features the following controls;

- Multi range timer with end of cycle audible alarm and automatic agitator shut off.
- Temperature indication and control with an accuracy $\pm 0.25\%$ of controller range. Display resolution 0.1°C.
- System control and calibration accuracy better than $\pm 1^\circ\text{C}$.
- Solid state relay for silent switching, reliability and zero electrical noise.
- Push button tank drainage with inline filter.
- Magnetically coupled drain pump for reliability.

Other design features include:-

- Process tank constructed in high-grade 316 stainless steel.
- Lid interlock and latch for added safety.
- Stainless steel bearing housing.
- Industrial quality motor specification.
- Level protection to disable heating.
- Easy access for servicing.
- Free standing machine on lockable wheels.



SDL ATLAS LLC
3934 Airway Drive
Rock Hill, SC 29732-9200, USA
Telephone: +1 803 329 2110
Website: www.sdatlas.com
Email: info@sdatlas.com

SDL ATLAS LTD.
1B, Building B, Junxiang Da Mansion
No. 9 Zhongshan Yuan Road, Nanshan
Shenzhen, 518052, P.R.C.
Telephone: +86 (755) 2671 1168
Website: www.sdatlas.com
Email: info@sdatlas.com.cn

SDL ATLAS LTD.
3J, Garment Centre, 576 Castle Peak Road,
Kowloon, Hong Kong.
Telephone: (852) 3443 4888
Website: www.sdatlas.com
Email: info@sdatlas.com.cn